

# 21.5" Fanless Touch Screen AIO PC



## Features

- ✓ Intel® Celeron Quad Core CPU, up to 2.6Ghz
- ✓ DDR4 SO-DIMM memory support up to 32GB
- ✓ Dual 4K display via HDMI and Display Port
- ✓ Wide Temperature support -40°C~ 80°C
- ✓ Operating System: Win10/11 64bit, Linux 64bit
- ✓ Optimized for Cloud & VDI solutions, VMware and Citrix

## Specification



Model	LT2141	LT21101
Processor	Intel® Celeron® Quad Core N4120 (4M cache, 1.1Ghz up to 2.6Ghz)	Intel® Celeron® Quad Core J6412 (1.5M L2 cache, 2Ghz up to 2.6Ghz)
System Memory	1 x DDR4 SO-DIMM, up to 8GB	1 x DDR4 SO-DIMM, up to 32GB
Panel	21.5" TFT Display, 1920(W) RGB x 1080(H)	
Touch Panel	5-wire Resistive Touch Panel, or 10 points Projected Capacitive Touch Panel	
Storage	1 x M.2 for SSD 2 x Serial ATA III 6Gh/s for 2.5" HDD/SSD	1 x mSATA for SSD/4G Module 1 x SATA3.0 for 2.5" HDD/SSD
Expansion Slot	M.2 for WiFi PCIe, supports Intel® CNVi	M.2 key_E for WiFi
Speaker	2 x 2W High Quality Speaker	
OS Support	Windows 10 64 bit, Win 10 IoT, Linux	
Power Adapter	19V@3.14A, 60W (opt. wide voltage input)	12V@5A, 60W (opt. wide voltage input)
I/O Interface		
Side I/O	2 x USB, 1 x Power Switch ( for panel power or system power)	
Rear I/O	1 x PS/2 KB, 1 x PS/2 Mouse, 1 x Audio (Line out/Line in/Mic in), 1 x LAN, 1 x Display Port, 4 x USB3.0, 2 x USB2.0, 1 x 19V DC-in, Kensington Lock, (opt. 2 x COM, 1 x LPT)	1 x Audio, 1 x HDMI, 1 x DP, 2 x LAN, 4 x USB3.2, 1 x 12V DC-in, Kensington Lock (opt. up to 6 x COM, 8 x USB)
Mechanical & Environment		
Operating Temp.	0°C to +35°C	-20°C to +60°C
Storage Temp.	-20°C to +60°C	-40°C to +80°C
Dimension	56 x 32.5 x 61.3 cm (22 x 12.6 x 24.1 inch) (without stand)	
Options	TPM 2M/5M Camera IP 65/IP43 water and dust protection Anti-Spy, Privacy Film Protector Anti-Bacterial (MRSA-resistant) VESA Bracket 75x75, 100x100 mm	