

23.8" High Performance Touch Screen AIO PC



Features

- ✓ Support Intel® core 6th/7th/10th/11th Gen Processor
- ✓ DDR4 memory support up to 64GB
- ✓ Up to four display support (2*HDMI, 2*Display Port)
- ✓ Single Touch or 10-point Multi Touch support
- ✓ Operating System: Win 11 64 bit, Win10 64bit, Linux 64bit
- ✓ Flexible installation supports panel, pole, wall, desktop mounting

Specification



Model	LT2471	LT2404T
Processor	11 th Gen Intel® Tiger Lake i3/i5/i7 processor	12 th Gen Intel® Alder Lake i3/i5/i7/Pentium processor
Chipset	Intel® Tiger Lake-UP3 SoC	Intel® H610 Express Chipset
Panel	23.8" TFT Display, 1920(W) RGB x 1080(H)	
Touch Panel	5-wire Resistive Touch Panel, or 10 points Projected Capacitive Touch Panel	
System Memory	2 x DDR4-3200Mhz SO-DIMM, up to 64GB	2 x DDR4 2666/2933 SO-DIMM, up to 64GB
Storage	1 x SATA III 6Gh/s for 2.5" HDD/SSD 1 x M.2 M-key 2242/2280, PCIe 4.0x4, NVME	2 x SATA 6Gb/s, 1 x M.2 2242/2280 SSD
Expansion Slot	M.2 E-key(2230)USB2.0/PClex1 support CNVi	1 x M.2 for WiFi
Speaker	2 x 2W High Quality Speaker	
OS Support	Win 10 64 bit, Win 8.1 64bit, Win 7, Linux	Win 11 64 bit, Win 10 64 bit, Win 10 IoT, Linux
Power Adapter	96~120W power adaptor	96~120W power adaptor
I/O Interface		
Side I/O	2 x USB, 1 x Power Switch	N/A
Rear I/O	2 xRJ-45, 2 x HDMI, 2 x DP, Line-out/MIC Combo DC in (12 – 24V), Kensington Lock Opt. 4xCOM (2*RS232/422/485, 2*RS232)	1 x Audio out, 1 x RJ-45, 1 x HDMI, 1 x VGA, 6 x USB, 1 x Mic in, 1 x Power Port,
Mechanical & Environment		
Operating Temp.	0°C to +60°C	0°C to +35°C
Storage Temp.	-20°C to +85°C	-20°C to +60°C
Dimension	502x307x 2 mm (19.7x12x2 inch) (w/o stand)	541x322x415mm (21x12.6x 6.2 inch) w/ stand
Options	TPM 2.0 3M Camera Anti-Spy, Privacy Film Protector Anti-Bacterial (MRSA-resistant) VESA Bracket 75x75, 100x100 mm Color: Apple white or Black Chassis: ABS Plastic or Metal chassis Up to 4 x independent 4K HDR Display or 2 x 8K SDR Displays (DP), LT2471 only	